



Safety Data Sheet

Section 1: Identification

Product Identifier • Conventional Gasoline with Ethanol

- Synonyms**
- Conventional Midgrade Unleaded Gasoline with Ethanol; Conventional Premium Unleaded Gasoline with Ethanol; Conventional Regular Unleaded Gasoline with Ethanol; E10-87; E10-89; E10-93; Midgrade Unleaded Gasoline with Ethanol; Premium Unleaded Gasoline with Ethanol; Regular Unleaded Gasoline with Ethanol

Relevant identified uses of the substance or mixture and uses advised against

- Recommended use** • Fuel
- Restrictions on use** • All others

Details of the supplier of the safety data sheet

- Manufacturer**
- Guttman Energy, Inc.
200 Speers Street
Belle Vernon, PA 15012
United States
www.guttmanenergyfuels.com
safety@guttmanenergy.com

Emergency telephone number

- Manufacturer** • 1-800-535-5053 - INFOTRAC

Section 2: Hazard Identification

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

- OSHA HCS 2012**
- Flammable Liquids 1
 - Acute Toxicity Oral 4
 - Aspiration 1
 - Skin Irritation 2
 - Eye Irritation 2
 - Acute Toxicity Inhalation 4
 - Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation
 - Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects
 - Germ Cell Mutagenicity 1B
 - Carcinogenicity 1A
 - Reproductive Toxicity 1B
 - Specific Target Organ Toxicity Repeated Exposure 1
 - Specific Target Organ Toxicity Repeated Exposure 2

Label elements

OSHA HCS 2012

DANGER



Hazard statements

- Extremely flammable liquid and vapor
- Harmful if swallowed
- May be fatal if swallowed and enters airways
- Causes skin irritation
- Causes serious eye irritation
- Harmful if inhaled
- May cause respiratory irritation
- May cause drowsiness or dizziness
- May cause genetic defects.
- May cause cancer.
- May damage fertility or the unborn child.
- Causes damage to organs through prolonged or repeated exposure.
- May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.
- Keep container tightly closed.
- Ground and/or bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Do not breathe mists, vapors, and/or spray.
- Wash thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Use only outdoors or in a well-ventilated area.
- Wear protective gloves/protective clothing/eye protection/face protection.

Response

- In case of fire: Use appropriate media for extinction.
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Call a POISON CENTER or doctor/physician if you feel unwell.
- If on skin: Wash with plenty of water .
- Specific treatment, see supplemental first aid information.
- Take off contaminated clothing and wash before reuse.
- If skin irritation occurs: Get medical advice/attention.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.
- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- Rinse mouth.
- Do NOT induce vomiting.
- IF exposed or concerned: Get medical advice/attention.
- Get medical advice/attention if you feel unwell.

Storage/Disposal

- Store in a well-ventilated place. Keep container tightly closed.
- Keep cool.
- Store locked up.

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Supplemental information

- 20 percent of this product consists of an ingredient of unknown toxicity via the inhalation route.

Other hazards

OSHA HCS 2012

- Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Other information

NFPA



Section 3 - Composition/Information on Ingredients

Substances

- Material does not meet the criteria of a substance.

Mixtures

Composition					
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments
Benzine (motor fuel)	CAS:86290-81-5	0% TO 100%	NDA	OSHA HCS 2012: Flam. Liq. 1; Asp. Tox. 1; Skin Irrit. 2; Eye Irrit. 2; Muta. 1B; Repr. 1B; STOT SE 3: Narc. & Resp. Irrit.; STOT RE 1 (CNS, Blood, Bone Marrow, Eyes); Carc. 1A; STOT RE 2 (Ear, Nervous System); Acute Tox. 4 (Orl); Acute Tox. 4 (Inhl)	NDA
Toluene	CAS:108-88-3	0% TO 26%	Ingestion/Oral-Rat LD50 • 636 mg/kg Inhalation-Rat LC50 • 49 g/m ³ 4 Hour(s) Skin-Rabbit LD50 • 14100 µL/kg	OSHA HCS 2012: Flam. Liq. 2; Acute Tox. 4 (Orl); Skin Irrit. 2; Eye Irrit. 2; Muta. 1B; Repr. 2; STOT SE 3: Narc.; STOT RE 1 (CNS, Inhl); Asp. Tox. 1	NDA
Xylene	CAS:1330-20-7	0% TO 22%	Ingestion/Oral-Rat LD50 • 4300 mg/kg Inhalation-Rat LC50 • 5000 ppm 4 Hour(s) Skin-Rabbit LD50 • >1700 mg/kg	OSHA HCS 2012: Flam. Liq. 3; Acute Tox. 4 (Inhl); Skin Irrit. 2; Eye Irrit. 2; Repr. 1B (Inhl); STOT SE 3: Narc.; STOT SE 3: Resp. Irrit.	NDA
Ethanol	CAS:64-17-5	0% TO 10%	Ingestion/Oral-Rat LD50 • 7060 mg/kg Inhalation-Rat LC50 • 124700 mg/m ³ 4 Hour(s)	OSHA HCS 2012: Flam. Liq. 2; Acute Tox. 3 (Inhl); Skin Irrit. 2; Eye Irrit. 2; Muta. 2; STOT SE 3: Narc.	NDA
Benzene	CAS:71-43-2	0% TO 10%	Ingestion/Oral-Rat LD50 • 930 mg/kg Skin-Rabbit LD50 • >9400 µL/kg	OSHA HCS 2012: Flam. Liq. 2; Acute Tox. 4 (Orl); Acute Tox. 4 (Inhl); Skin Irrit. 2; Eye Irrit. 2; Muta. 1B (Orl, Inhl); Carc. 1A (Inhl); Repr. 2 (Inhl); STOT SE 3:	NDA

Conventional Gasoline with Ethanol

				Narc. (Inhl); STOT RE 1 (Blood, Bone marrow / Inhl); Asp. Tox. 1	
Cyclohexane	CAS:110-82-7	0% TO 7%	Ingestion/Oral-Rat LD50 • 6240 mg/kg Skin-Rabbit LD50 • >2000 mg/kg	OSHA HCS 2012: Flam. Liq. 2; Eye Irrit. 2; STOT SE 3: Narc.; Skin Irrit. 2; Asp. Tox. 1	NDA
1,2,4-Trimethylbenzene	CAS:95-63-6	0% TO 5%	Ingestion/Oral-Rat LD50 • 5 g/kg Inhalation-Rat LC50 • 18000 mg/m ³ 4 Hour(s)	OSHA HCS 2012: Flam. Liq. 3; Skin Irrit. 2; Eye Irrit. 2; STOT SE 3: Resp. Irrit.; STOT SE 3: Narc.; Asp. Tox. 1;	NDA
Naphthalene	CAS:91-20-3	0% TO 4%	Skin-Rabbit LD50 • >20 g/kg Ingestion/Oral-Rat LD50 • 490 mg/kg	OSHA HCS 2012: Flam. Sol. 2; Acute Tox. 4 (Orl); Skin Irrit. 2; Muta. 2; Carc. 2; Repr. 2; STOT SE 3: Narc.; STOT RE 1 (Blood, Eyes; Orl, Inhl)	NDA
Ethylbenzene	CAS:100-41-4	0% TO 4%	Ingestion/Oral-Rat LD50 • 3500 mg/kg Inhalation-Rat LC50 • 55000 mg/m ³ 2 Hour(s) Skin-Rabbit LD50 • >5000 mg/kg	OSHA HCS 2012: Flam. Liq. 2; Acute Tox. 4 (Inhl); Eye Irrit. 2; Carc. 2 (Inhl); Repr. 2 (Inhl); STOT SE 3: Narc.; STOT SE 3: Resp. Irrit. (Inhl); STOT RE 2 (Ear / Inhl); Asp. Tox. 1	NDA
Hexane	CAS:110-54-3	0% TO 3%	Ingestion/Oral-Rat LD50 • 25 g/kg Inhalation-Rat LC50 • 48000 ppm 4 Hour(s)	OSHA HCS 2012: Flam. Liq. 2; Repr. 2; STOT RE 2 (CNS & Nervous System); Skin Irrit. 2; Eye Irrit. 2; STOT SE 3: Narc. & Resp. Irrit.; Asp. Tox. 1	NDA

Section 4: First Aid Measures

Description of first aid measures

- Inhalation** • Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing.
- Skin** • In case of contact with substance, immediately flush skin with running water for at least 20 minutes. Remove and isolate contaminated clothing. Wash skin with soap and water. If skin irritation occurs: Get medical advice/attention.
- Eye** • In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.
- Ingestion** • Rinse mouth. Do NOT induce vomiting. Obtain medical attention immediately if ingested.

Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

- Notes to Physician** • All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5: Fire Fighting Measures

Extinguishing media

Suitable Extinguishing Media • CAUTION: For mixtures containing a high percentage of an alcohol or polar solvent, alcohol-resistant foam may be more effective.
SMALL FIRES: Dry chemical, CO₂, water spray or alcohol-resistant foam.
LARGE FIRES: Water spray, fog or alcohol-resistant foam.

Unsuitable Extinguishing Media • Avoid using direct water stream.

Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards • HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.
Containers may explode when heated.
Many liquids are lighter than water.
Vapors may form explosive mixtures with air.
Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).
Vapors may travel to source of ignition and flash back.
Vapor explosion hazard indoors, outdoors or in sewers.
Runoff to sewer may create fire or explosion hazard.

Hazardous Combustion Products • No data available

Advice for firefighters

- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.
Move containers from fire area if you can do it without risk.
LARGE FIRES: Cool containers with flooding quantities of water until well after fire is out.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions • CAUTION: Victim may be a source of contamination. Do not walk through spilled material. Use appropriate Personal Protective Equipment (PPE)

Emergency Procedures • As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions. LARGE SPILL: Consider initial downwind evacuation for at least 300 meters (1000 feet) ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

Environmental precautions

- Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Containment/Clean-up Measures • Stop leak if you can do it without risk.
Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
Use clean non-sparking tools to collect absorbed material.
A vapor suppressing foam may be used to reduce vapors.
All equipment used when handling the product must be grounded.
LARGE SPILLS: Dike far ahead of spill for later disposal.

LARGE SPILLS: Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Section 7 - Handling and Storage

Precautions for safe handling

Handling • Keep away from heat, sparks, and flame. Do not use sparking tools. Take precautionary measures against static charges. All equipment used when handling the product must be grounded. Do not breathe mist, vapors and/or spray. Avoid contact with skin, eyes or clothing. Wear appropriate personal protective equipment, avoid direct contact. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco.

Conditions for safe storage, including any incompatibilities

Storage • Store in a tightly closed container. Store in a cool/low-temperature, well-ventilated place.

Section 8 - Exposure Controls/Personal Protection

Control parameters

	Result	Exposure Limits/Guidelines		
		ACGIH	NIOSH	OSHA
Toluene (108-88-3)	Ceilings	Not established	Not established	300 ppm Ceiling
	TWAs	20 ppm TWA	100 ppm TWA; 375 mg/m3 TWA	200 ppm TWA
	STELs	Not established	150 ppm STEL; 560 mg/m3 STEL	Not established
Benzene (71-43-2)	Ceilings	Not established	Not established	25 ppm Ceiling
	STELs	2.5 ppm STEL	1 ppm STEL	5 ppm STEL (see 29 CFR 1910.1028)
	TWAs	0.5 ppm TWA	0.1 ppm TWA	10 ppm TWA (applies to industry segments exempt from the benzene standard at 29 CFR 1910.1028); 1 ppm TWA
Naphthalene (91-20-3)	TWAs	10 ppm TWA	10 ppm TWA; 50 mg/m3 TWA	10 ppm TWA; 50 mg/m3 TWA
	STELs	Not established	15 ppm STEL; 75 mg/m3 STEL	Not established
Cyclohexane (110-82-7)	TWAs	100 ppm TWA	300 ppm TWA; 1050 mg/m3 TWA	300 ppm TWA; 1050 mg/m3 TWA
Ethylbenzene (100-41-4)	TWAs	20 ppm TWA	100 ppm TWA; 435 mg/m3 TWA	100 ppm TWA; 435 mg/m3 TWA
	STELs	Not established	125 ppm STEL; 545 mg/m3 STEL	Not established
Xylene (1330-20-7)	TWAs	100 ppm TWA	Not established	100 ppm TWA; 435 mg/m3 TWA
	STELs	150 ppm STEL	Not established	Not established
Ethanol (64-17-5)	TWAs	Not established	1000 ppm TWA; 1900 mg/m3 TWA	1000 ppm TWA; 1900 mg/m3 TWA
	STELs	1000 ppm STEL	Not established	Not established
Hexane (110-54-3)	TWAs	50 ppm TWA	50 ppm TWA; 180 mg/m3 TWA	500 ppm TWA; 1800 mg/m3 TWA
Benzine (motor fuel) (86290-81-5)	STELs	500 ppm STEL	Not established	Not established
	TWAs	300 ppm TWA	Not established	Not established
1,2,4-Trimethylbenzene (95-63-6)	TWAs	Not established	25 ppm TWA; 125 mg/m3 TWA	Not established

Exposure controls

Engineering Measures/Controls

- Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof electrical/ventilating/lighting/equipment.

Personal Protective Equipment

Respiratory

- Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced. Organic vapor chemical cartridge or supplied air respirators should be worn for exposures to any components exceeding the established exposure limits.

Eye/Face

- Wear safety goggles.

Skin/Body

- Use nitrile rubber, viton or PVA gloves for repeated or prolonged skin exposure. Wear long sleeves and/or protective coveralls.

General Industrial Hygiene Considerations

- Always handle products in accordance with best industrial hygiene and safety practices in mind, specifically avoiding contact with skin, eyes and clothing.

Environmental Exposure Controls

- Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways. Follow best practice for site management and disposal of waste.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

STEL = Short Term Exposure Limits are based on 15-minute exposures

NIOSH = National Institute of Occupational Safety and Health

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

OSHA = Occupational Safety and Health Administration

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Appearance/Description	Clear or colored liquid with strong hydrocarbon odor.
Color	Clear or colored.	Odor	Strong hydrocarbon odor.
Odor Threshold	No data available		
General Properties			
Boiling Point	70 to 437 F(21.1111 to 225 C)	Melting Point/Freezing Point	No data available
Decomposition Temperature	No data available	pH	No data available
Specific Gravity/Relative Density	0.66 to 0.78 Water=1	Water Solubility	Slightly Soluble 0 to 1 %
Viscosity	No data available		
Volatility			
Vapor Pressure	No data available	Vapor Density	3 to 4 Air=1
Evaporation Rate	No data available	Volatiles (Wt.)	100 %
Volatiles (Vol.)	100 %		
Flammability			
Flash Point	-50 F(-45.5556 C) PMCC (Pensky-Martins Closed Cup)	UEL	7.6 %
LEL	1.4 %	Autoignition	No data available
Flammability (solid, gas)	No data available		
Environmental			

Octanol/Water Partition coefficient	No data available		
-------------------------------------	-------------------	--	--

Section 10: Stability and Reactivity

Reactivity

- No dangerous reaction known under conditions of normal use.

Chemical stability

- Stable under normal temperatures and pressures.

Possibility of hazardous reactions

- Hazardous polymerization not indicated.

Conditions to avoid

- Keep away from heat, sparks, and flame.

Incompatible materials

- No data available

Hazardous decomposition products

- No data available

Section 11 - Toxicological Information

Information on toxicological effects

		Components
Benzene (motor fuel) (0% TO 100%)	86290-81-5	Acute Toxicity: Ingestion/Oral-Rat LD50 • 13.6 g/kg; <i>Behavioral:Headache; Lungs, Thorax, or Respiration:Cough; Sense Organs and Special Senses:Eye:Conjunctive irritation;</i> Mutagen: Unscheduled DNA synthesis • Ingestion/Oral-Mammal • 100 mg/kg; Sperm Morphology • Inhalation-Rat • 300 mg/m ³ 10 Week(s)-Intermittent; Reproductive: Inhalation-Rat TClO • 300 mg/m ³ (1-19D preg); <i>Reproductive Effects:Specific Developmental Abnormalities:Musculoskeletal system; Reproductive Effects:Effects on Newborn:Behavioral; Reproductive Effects:Effects on Newborn:Physical</i>
Toluene (0% TO 26%)	108-88-3	Acute Toxicity: Ingestion/Oral-Rat LD50 • 636 mg/kg; Inhalation-Rat LC50 • 49 g/m ³ 4 Hour(s); Inhalation-Human TClO • 200 ppm; <i>Brain and Coverings:Recordings from specific areas of CNS;</i> <i>Behavioral:Antipsychotic; Blood:Changes in bone marrow not included above;</i> Inhalation-Human TClO • 1500 mg/m ³ 8 Hour(s); <i>Sense Organs and Special Senses:Eye:Lacrimation; Sense Organs and Special Senses:Eye:Conjunctive irritation; Behavioral:Ataxia;</i> Inhalation-Man TClO • 50 ppm; <i>Kidney, Ureter, and Bladder:Other changes in urine composition;</i> Skin-Rabbit LD50 • 14100 µL/kg; Irritation: Eye-Rabbit • 2 mg 24 Hour(s) • Severe irritation; Skin-Rabbit • 20 mg 24 Hour(s) • Moderate irritation; Multi-dose Toxicity: Inhalation-Mouse TClO • 250 ppm 4 Day(s)-Continuous; <i>Behavioral:Convulsions or effect on seizure threshold; Behavioral:Abuse;</i> Inhalation-Mouse TClO • 50 ppm 12 Week(s)-Intermittent; <i>Brain and Coverings:Other degenerative changes;</i> Inhalation-Rat TClO • 10 ppm 6 Hour(s) 13 Week(s)-Intermittent; <i>Brain and Coverings:Other degenerative changes; Biochemical:Enzyme inhibition, induction, or change in blood or tissue levels:Multiple enzyme effects;</i> Mutagen: Micronucleus test • Ingestion/Oral-Mouse • 200 mg/kg; Sister chromatid exchange • Inhalation-Human • 252 µg/L 19 Year(s); Cytogenetic analysis • Inhalation-Rat • 5400 µg/m ³ 16 Week(s)-Intermittent; Reproductive: Inhalation-Mouse TClO • 500 mg/m ³ 24 Hour(s)(6-13D preg); <i>Reproductive Effects:Effects on Embryo or Fetus:Fetotoxicity (except death, e.g., stunted fetus);</i> Inhalation-Mouse TClO • 200 ppm 7 Hour(s)(7-16D preg); <i>Reproductive Effects:Specific Developmental Abnormalities:Urogenital system</i>
1,2,4-Trimethylbenzene (0% TO 5%)	95-63-6	Acute Toxicity: Ingestion/Oral-Rat LD50 • 5 g/kg; Inhalation-Rat LC50 • 18000 mg/m ³ 4 Hour(s); Mutagen: Sister chromatid exchange • Intraperitoneal-Mouse • 900 mg/kg

Conventional Gasoline with Ethanol

Xylene (0% TO 22%)	1330-20-7	<p>Acute Toxicity: Ingestion/Oral-Rat LD50 • 4300 mg/kg; <i>Liver:Other changes; Kidney, Ureter, and Bladder:Other changes;</i> Inhalation-Rat LC50 • 5000 ppm 4 Hour(s); Inhalation-Man LCLo • 10000 ppm 6 Hour(s); <i>Behavioral:General anesthetic; Lungs, Thorax, or Respiration:Cyanosis; Blood:Other changes;</i> Inhalation-Human TCLo • 200 ppm; <i>Sense Organs and Special Senses:Olfaction:Other changes; Sense Organs and Special Senses:Eye:Conjunctive irritation; Lungs, Thorax, or Respiration:Other changes;</i> Skin-Rabbit LD50 • >1700 mg/kg; Irritation: Eye-Rabbit • 5 mg 24 Hour(s) • Severe irritation; Skin-Rabbit • 500 mg 24 Hour(s) • Moderate irritation; Reproductive: Inhalation-Mouse TCLo • 1 g/m³ 12 Hour(s)(6-15D preg); <i>Reproductive Effects:Effects on Embryo or Fetus:Fetotoxicity (except death, e.g., stunted fetus); Reproductive Effects:Specific Developmental Abnormalities:Musculoskeletal system;</i> Inhalation-Rat TCLo • 50 mg/m³ 6 Hour(s)(1-21D preg); <i>Reproductive Effects:Effects on Fertility:Post-implantation mortality; Reproductive Effects:Effects on Embryo or Fetus:Fetotoxicity (except death, e.g., stunted fetus); Reproductive Effects:Specific Developmental Abnormalities:Craniofacial (including nose and tongue)</i></p>
Benzene (0% TO 10%)	71-43-2	<p>Acute Toxicity: Ingestion/Oral-Rat LD50 • 930 mg/kg; <i>Behavioral:Tremor; Behavioral:Convulsions or effect on seizure threshold;</i> Ingestion/Oral-Man LDLo • 50 mg/kg; Inhalation-Rat LC50 • 10000 ppm 7 Hour(s); Inhalation-Rat TCLo • 1 ppm 6 Hour(s); <i>Kidney, Ureter, and Bladder:Other changes in urine composition;</i> Skin-Rabbit LD50 • >9400 µL/kg; Irritation: Eye-Rabbit • 2 mg 24 Hour(s) • Severe irritation; Skin-Rabbit • 20 mg 24 Hour(s) • Moderate irritation; Multi-dose Toxicity: Inhalation-Mouse TCLo • 100 ppm 2 Week(s)-Intermittent; <i>Endocrine:Differential effect of sex or castration on observed toxicity; Blood:Leukopenia; Blood:Changes in bone marrow not included above;</i> Inhalation-Mouse TDLo • 100 ppm 6 Hour(s) 10 Day(s)-Intermittent; <i>Blood:Changes in other cell count (unspecified); Blood:Changes in leucocyte (WBC) count; Blood:Changes in erythrocyte (RBC) count;</i> Mutagen: Dominant lethal test • Ingestion/Oral-Mouse • 1 mg/kg; Cytogenetic analysis • Inhalation-Human • 125 ppm 1 Year(s); Cytogenetic analysis • Inhalation-Human • 0.1 ppm; Sister chromatid exchange • Inhalation-Mouse • 10 ppm 6 Hour(s); Micronucleus test • Inhalation-Rat • 1 ppm 6 Hour(s); Reproductive: Inhalation-Mouse TCLo • 20 ppm 6 Hour(s)(6-15D preg); <i>Reproductive Effects:Specific Developmental Abnormalities:Blood and lymphatic system;</i> Inhalation-Mouse TCLo • 5 ppm (6-15D preg); <i>Reproductive Effects:Effects on Embryo or Fetus:Cytological changes; Reproductive Effects:Specific Developmental Abnormalities:Blood and lymphatic system;</i> Inhalation-Rat TCLo • 670 mg/m³ 24 Hour(s)(15D pre/1-22D preg); <i>Reproductive Effects:Effects on Fertility:Female fertility index;</i> Parenteral-Mouse TDLo • 4 g/kg (12D preg); <i>Reproductive Effects:Effects on Newborn:Weaning or lactation index;</i> Tumorigen / Carcinogen: Ingestion/Oral-Rat • 10 g/kg 52 Week(s)-Intermittent; <i>Tumorigenic:Carcinogenic by RTECS criteria; Endocrine:Tumors; Blood:Leukemia;</i> Inhalation-Human • 150 ppm 15 Minute(s) 8 Year(s)-Intermittent; <i>Tumorigenic:Carcinogenic by RTECS criteria; Blood:Leukemia</i></p>
Ethylbenzene (0% TO 4%)	100-41-4	<p>Acute Toxicity: Ingestion/Oral-Rat LD50 • 3500 mg/kg; Inhalation-Guinea Pig LCLo • 2500 ppm 8 Hour(s); <i>Behavioral:Coma;</i> Inhalation-Mouse TCLo • 600 ppm 6 Minute(s); <i>Lungs, Thorax, or Respiration:Respiratory depression;</i> Skin-Rabbit LD50 • 17800 µL/kg; Irritation: Eye-Rabbit • 500 mg • Severe irritation; Skin-Rabbit • 15 mg 24 Hour(s)-Open • Mild irritation; Multi-dose Toxicity: Inhalation-Rat TCLo • 550 ppm 8 Hour(s) 5 Day(s)-Intermittent; <i>Sense Organs and Special Senses:Ear:Change in acuity; Sense Organs and Special Senses:Ear:Changes in cochlear structure or function;</i> Inhalation-Rat TDLo • 200 ppm 13 Week(s)-Intermittent; <i>Sense Organs and Special Senses:Ear:Changes in cochlear structure or function;</i> Mutagen: Specific locus test • Intraperitoneal-Mouse • 754 µmol/L; Micronucleus test • Unreported Route-Hamster • Embryo (Somatic cell) • 25 mg/L; Sister chromatid exchange • Unreported Route-Human • Lymphocyte (Somatic cell) • 10 mmol/L; Mutation in Mammalian Somatic Cells • Unreported Route-Mouse • Lymphocyte (Somatic cell) • 80 mg/L; Reproductive: Inhalation-Rabbit TCLo • 1 g/m³ 24 Hour(s)(7-20D preg); <i>Reproductive Effects:Effects on Fertility:Abortion;</i> Inhalation-Rat TCLo • 1000 ppm (6-20D preg); <i>Reproductive Effects:Effects on Embryo or Fetus:Fetotoxicity (except death, e.g., stunted fetus);</i> Inhalation-Rat TCLo • 600 mg/m³ 24 Hour(s)(7-15D preg); <i>Reproductive Effects:Effects on Fertility:Post-implantation mortality; Reproductive Effects:Effects on Embryo or Fetus:Fetal death; Reproductive Effects:Specific Developmental Abnormalities:Musculoskeletal system;</i> Inhalation-Rat TCLo • 96 ppm 7 Hour(s)(1-19D preg); <i>Reproductive Effects:Specific Developmental Abnormalities:Musculoskeletal system;</i> Tumorigen / Carcinogen: Inhalation-Mouse TCLo • 750 ppm 6 Hour(s) 2 Year(s)-Intermittent; <i>Tumorigenic:Carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration:Bronchiogenic carcinoma; Liver:Tumors;</i> Inhalation-Rat TCLo • 23400 mg/kg 104 Week(s)-Intermittent; <i>Tumorigenic:Equivocal tumorigenic agent by RTECS criteria; Kidney, Ureter, and Bladder:Kidney tumors; Reproductive Effects:Tumorigenic Effects:Testicular tumors;</i> Inhalation-Rat TCLo • 750 ppm 6 Hour(s) 2 Year(s)-Intermittent; <i>Tumorigenic:Carcinogenic by RTECS criteria; Kidney, Ureter, and Bladder:Tumors</i></p>
Naphthalene (0% TO 4%)	91-20-3	<p>Acute Toxicity: Ingestion/Oral-Rat LD50 • 490 mg/kg; Ingestion/Oral-Mouse TDLo • 158 mg/kg; <i>Brain and Coverings:Other degenerative changes; Liver:Other changes; Biochemical:Metabolism (intermediary):Lipids, including transport;</i> Inhalation-Human TCLo • 250 mg/m³; <i>Sense Organs and Special Senses:Eye:Lacrimation; Behavioral:Headache;</i> Skin-Rabbit LD50 • >20 g/kg; Unreported-Guinea Pig LD50 • 1200 mg/kg; <i>Behavioral:Somnolence (general depressed activity);</i></p>

Conventional Gasoline with Ethanol

		<p>Irritation: Skin-Rabbit • 0.05 mL 24 Hour(s) • Severe irritation; Multi-dose Toxicity: Ingestion/Oral-Rat TDLo • 4500 mg/kg 10 Day(s)-Intermittent; <i>Brain and Coverings:Other degenerative changes;</i> Ingestion/Oral-Rat TDLo • 500 mg/kg 10 Day(s)-Intermittent; <i>Behavioral:Sleep; Lungs, Thorax, or Respiration:Dyspnea;</i> Mutagen: Specific locus test • Inhalation-Rat • 30 ppm 13 Week(s)-Intermittent; Micronucleus test • Unreported Route-Human • Lymphocyte (Somatic cell) • 30 mg/L; Reproductive: Ingestion/Oral-Mouse TDLo • 2400 mg/kg (7-14D preg); <i>Reproductive Effects:Effects on Newborn:Live birth index; Reproductive Effects:Effects on Newborn:Viability index (e.g., # alive at day 4 per # born alive);</i> Ingestion/Oral-Rat TDLo • 4500 mg/kg (6-15D preg); <i>Reproductive Effects:Effects on Embryo or Fetus:Fetotoxicity (except death, e.g., stunted fetus); Reproductive Effects:Specific Developmental Abnormalities:Other developmental abnormalities;</i> Tumorigen / Carcinogen: Inhalation-Mouse TCLo • 30 ppm 6 Hour(s) 2 Year(s)-Intermittent; <i>Tumorigenic:Neoplastic by RTECS criteria; Lungs, Thorax, or Respiration:Tumors;</i> Inhalation-Rat TCLo • 60 ppm 6 Hour(s) 105 Week(s)-Intermittent; <i>Tumorigenic:Carcinogenic by RTECS criteria; Sense Organs and Special Senses:Olfaction:Tumors;</i> Inhalation-Rat TCLo • 1575 mg/kg 105 Week(s)-Intermittent; <i>Tumorigenic:Carcinogenic by RTECS criteria; Sense Organs and Special Senses:Olfaction:Tumors</i></p>
Hexane (0% TO 3%)	110-54-3	<p>Acute Toxicity: Ingestion/Oral-Rat LD50 • 25 g/kg; Inhalation-Rat LC50 • 48000 ppm 4 Hour(s); Irritation: Eye-Rabbit • 10 mg • Mild irritation; Reproductive: Inhalation-Rat TCLo • 5000 ppm (6-19D preg); <i>Reproductive Effects:Specific Developmental Abnormalities:Musculoskeletal system; Reproductive Effects:Specific Developmental Abnormalities:Urogenital system</i></p>
Cyclohexane (0% TO 7%)	110-82-7	<p>Acute Toxicity: Ingestion/Oral-Rat LD50 • 6240 mg/kg; <i>Behavioral:Somnolence (general depressed activity); Gastrointestinal:Changes in structure or function of salivary glands; Gastrointestinal:Hypermotility, diarrhea;</i> Irritation: Skin-Rabbit • 1548 mg 2 Day(s)-Intermittent; Multi-dose Toxicity: Inhalation-Mouse TCLo • 2000 ppm 90 Day(s)-Intermittent; <i>Behavioral:Somnolence (general depressed activity); Behavioral:Changes in motor activity (specific assay)</i></p>
Ethanol (0% TO 10%)	64-17-5	<p>Acute Toxicity: Ingestion/Oral-Rat LD50 • 7 g/kg; Ingestion/Oral-Human TDLo • 0.5 g/kg; <i>Behavioral:Somnolence (general depressed activity); Behavioral:Changes in psychophysiological tests;</i> Ingestion/Oral-Man TDLo • 3371 µL/kg; <i>Behavioral:Altered sleep time (including change in righting reflex); Behavioral:Excitement; Behavioral:Coma;</i> Ingestion/Oral-Rat TDLo • 8000 mg/kg; <i>Brain and Coverings:Other degenerative changes; Cardiac:Cardiomyopathy including infarction; Liver:Multiple effects;</i> Inhalation-Rat LC50 • 5900 mg/m³ 6 Hour(s); Irritation: Eye-Rabbit • 500 mg • Severe irritation; Skin-Rabbit • 20 mg 24 Hour(s) • Moderate irritation; Multi-dose Toxicity: Ingestion/Oral-Rat TDLo • 188 g/kg 25 Day(s)-Intermittent; <i>Liver:Fatty liver degeneration; Biochemical:Enzyme inhibition, induction, or change in blood or tissue levels:Multiple enzyme effects; Biochemical:Metabolism (intermediary):Lipids, including transport;</i> Mutagen: Cytogenetic analysis • Ingestion/Oral-Human • 49014 g/kg 25 Year(s); Dominant lethal test • Ingestion/Oral-Mouse • 3720 mg/kg 3 Day(s); Sperm Morphology • Ingestion/Oral-Mouse • 1500 mg/kg 50 Day(s); Reproductive: Ingestion/Oral-Rat TDLo • 12 g/kg (9-12D preg); <i>Reproductive Effects:Effects on Embryo or Fetus:Fetotoxicity (except death, e.g., stunted fetus);</i> Ingestion/Oral-Woman TDLo • 5860 mL/kg (3Y pre-100D post); <i>Reproductive Effects:Specific Developmental Abnormalities:Craniofacial (including nose and tongue); Reproductive Effects:Effects on Newborn:Behavioral; Reproductive Effects:Effects on Newborn:Delayed effects;</i> Tumorigen / Carcinogen: Ingestion/Oral-Mouse • 400 g/kg 57 Week(s)-Intermittent; <i>Tumorigenic:Equivocal tumorigenic agent by RTECS criteria; Gastrointestinal:Tumors;</i> Ingestion/Oral-Mouse TDLo • 320 mg/kg 50 Week(s)-Intermittent; <i>Tumorigenic:Equivocal tumorigenic agent by RTECS criteria; Liver:Tumors; Blood:Lymphoma, including Hodgkin's disease</i></p>

GHS Properties	Classification
Respiratory sensitization	OSHA HCS 2012•No data available
Serious eye damage/Irritation	OSHA HCS 2012•Eye Irritation 2
Acute toxicity	OSHA HCS 2012•Acute Toxicity - Inhalation 4 - ATEmix(inhl, vapors) = 17.68 mg/L; Acute Toxicity - Oral 4 - ATEmix(oral) = 1491.30 mg/kg
Aspiration Hazard	OSHA HCS 2012•Aspiration 1
Carcinogenicity	OSHA HCS 2012•Carcinogenicity 1A
Germ Cell Mutagenicity	OSHA HCS 2012•Germ Cell Mutagenicity 1B
Skin corrosion/Irritation	OSHA HCS 2012•Skin Irritation 2
Skin sensitization	OSHA HCS 2012•No data available

STOT-RE	OSHA HCS 2012 •Specific Target Organ Toxicity Repeated Exposure 1; Specific Target Organ Toxicity Repeated Exposure 2
STOT-SE	OSHA HCS 2012 •Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects; Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation
Toxicity for Reproduction	OSHA HCS 2012 •Toxic to Reproduction 1B

Potential Health Effects

Inhalation

- Acute (Immediate)** • Harmful if inhaled. May cause respiratory irritation. May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death.
- Chronic (Delayed)** • No data available

Skin

- Acute (Immediate)** • Causes skin irritation.
- Chronic (Delayed)** • No data available

Eye

- Acute (Immediate)** • Causes serious eye irritation.
- Chronic (Delayed)** • No data available

Ingestion

- Acute (Immediate)** • Harmful if swallowed. Material may be aspirated into lungs during ingestion and/or subsequent vomiting. Aspiration of this material will cause severe lung injury, chemical pneumonitis, pulmonary edema or death.
- Chronic (Delayed)** • No data available

Other

- Chronic (Delayed)** • CNS depression has been reported to occur in chronic abusers exposed to high levels of toluene. Symptoms include drowsiness, ataxia, tremors, cerebral atrophy, nystagmus (involuntary eye movements), and impaired speech, hearing, and vision. Neurobehavioral effects have been observed in occupationally exposed workers. Chronic exposure to benzene, a component of this material, results primarily in hematotoxicity, including aplastic anemia, pancytopenia, or any combination of anemia, leukopenia, and thrombocytopenia Chronic benzene exposure is associated with an increased risk of leukemia. Chronic exposure of workers to naphthalene has been reported to cause cataracts and retinal hemorrhage. Hexane may have effects on the central nervous system and especially peripheral nervous system, resulting in polyneuropathy. Exposure to relatively low concentrations of ethylbenzene for several days to weeks resulted in potentially irreversible damage to the inner ear and hearing of animals.

- Mutagenic Effects** • Repeated and prolonged exposure may cause mutagenic effects.

- Carcinogenic Effects** • Repeated and prolonged exposure may cause cancer.

Carcinogenic Effects				
	CAS	OSHA	IARC	NTP
Benzene	71-43-2	Specifically Regulated Carcinogen	Group 1-Carcinogenic	Known Human Carcinogen
Benzine (motor fuel)	86290-81-5	Not Listed	Group 2B-Possible Carcinogen	Not Listed
Ethylbenzene	100-41-4	Not Listed	Group 2B-Possible Carcinogen	Not Listed

Naphthalene	91-20-3	Not Listed	Group 2B-Possible Carcinogen	Reasonably Anticipated to be Human Carcinogen
-------------	---------	------------	------------------------------	---

Reproductive Effects • Repeated and prolonged exposure may cause reproductive effects.

Key to abbreviations

- LC = Lethal Concentration
- LD = Lethal Dose
- TC = Toxic Concentration
- TD = Toxic Dose

Section 12 - Ecological Information

Toxicity

- Non-mandatory section information about this substance not compiled for this reason.

Persistence and degradability

- Non-mandatory section information about this substance not compiled for this reason.

Bioaccumulative potential

- Non-mandatory section information about this substance not compiled for this reason.

Mobility in Soil

- Non-mandatory section information about this substance not compiled for this reason.

Other adverse effects

- Non-mandatory section information about this substance not compiled for this reason.

Section 13 - Disposal Considerations

Waste treatment methods

- Product waste** • Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.
- Packaging waste** • Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	UN number	UN proper shipping name	Transport hazard class(es)	Packing group	Environmental hazards
DOT	UN1203	Gasohol, Flammable Liquids n.o.s.	3	II	NDA

Special precautions for user • None specified.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code • No data available

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications

• Acute, Chronic, Fire

Inventory		
Component	CAS	TSCA
1,2,4-Trimethylbenzene	95-63-6	Yes
Benzene	71-43-2	Yes
Benzine (motor fuel)	86290-81-5	No
Cyclohexane	110-82-7	Yes
Ethanol	64-17-5	Yes
Ethylbenzene	100-41-4	Yes
Hexane	110-54-3	Yes
Naphthalene	91-20-3	Yes
Toluene	108-88-3	Yes
Xylene	1330-20-7	Yes

United States

Labor

U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals

•Naphthalene	91-20-3	Not Listed
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	Not Listed
•Toluene	108-88-3	Not Listed
•Xylene	1330-20-7	Not Listed
•Benzene	71-43-2	Not Listed
•Ethanol	64-17-5	Not Listed
•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	86290-81-5	Not Listed

U.S. - OSHA - Specifically Regulated Chemicals

•Naphthalene	91-20-3	Not Listed
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	Not Listed
•Toluene	108-88-3	Not Listed
•Xylene	1330-20-7	Not Listed
•Benzene	71-43-2	5 ppm STEL (See 29 CFR 1910.1028, 15 min); 0.5 ppm Action Level; 1 ppm TWA
•Ethanol	64-17-5	Not Listed
•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	86290-81-5	Not Listed

Environment

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

•Naphthalene	91-20-3	
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	(listed under Ethyl benzene)
•Toluene	108-88-3	
•Xylene	1330-20-7	(isomers and mixtures)

Conventional Gasoline with Ethanol

•Benzene	71-43-2	(including Benzene from gasoline)
•Ethanol	64-17-5	Not Listed
•Hexane	110-54-3	
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	86290-81-5	Not Listed
U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities		
•Naphthalene	91-20-3	100 lb final RQ; 45.4 kg final RQ
•Cyclohexane	110-82-7	1000 lb final RQ; 454 kg final RQ
•Ethylbenzene	100-41-4	1000 lb final RQ; 454 kg final RQ
•Toluene	108-88-3	1000 lb final RQ; 454 kg final RQ
•Xylene	1330-20-7	100 lb final RQ; 45.4 kg final RQ
•Benzene	71-43-2	10 lb final RQ (received an adjusted RQ of 10 lbs based on potential carcinogenicity in an August 14, 1989 final rule); 4.54 kg final RQ (received an adjusted RQ of 10 lbs based on potential carcinogenicity in an August 14, 1989 final rule)
•Ethanol	64-17-5	Not Listed
•Hexane	110-54-3	5000 lb final RQ; 2270 kg final RQ
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	86290-81-5	Not Listed
U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities		
•Naphthalene	91-20-3	Not Listed
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	Not Listed
•Toluene	108-88-3	Not Listed
•Xylene	1330-20-7	Not Listed
•Benzene	71-43-2	Not Listed
•Ethanol	64-17-5	Not Listed
•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	86290-81-5	Not Listed
U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs		
•Naphthalene	91-20-3	Not Listed
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	Not Listed
•Toluene	108-88-3	Not Listed
•Xylene	1330-20-7	Not Listed
•Benzene	71-43-2	Not Listed
•Ethanol	64-17-5	Not Listed
•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	86290-81-5	Not Listed
U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs		
•Naphthalene	91-20-3	Not Listed
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	Not Listed
•Toluene	108-88-3	Not Listed
•Xylene	1330-20-7	Not Listed
•Benzene	71-43-2	Not Listed
•Ethanol	64-17-5	Not Listed

Conventional Gasoline with Ethanol

•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	86290-81-5	Not Listed

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

•Naphthalene	91-20-3	0.1 % de minimis concentration
•Cyclohexane	110-82-7	1.0 % de minimis concentration
•Ethylbenzene	100-41-4	0.1 % de minimis concentration
•Toluene	108-88-3	1.0 % de minimis concentration
•Xylene	1330-20-7	1.0 % de minimis concentration
•Benzene	71-43-2	0.1 % de minimis concentration
•Ethanol	64-17-5	Not Listed
•Hexane	110-54-3	1.0 % de minimis concentration
•1,2,4-Trimethylbenzene	95-63-6	1.0 % de minimis concentration
•Benzine (motor fuel)	86290-81-5	Not Listed

U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing

•Naphthalene	91-20-3	Not Listed
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	Not Listed
•Toluene	108-88-3	Not Listed
•Xylene	1330-20-7	Not Listed
•Benzene	71-43-2	Not Listed
•Ethanol	64-17-5	Not Listed
•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	86290-81-5	Not Listed

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

•Naphthalene	91-20-3	carcinogen, initial date 4/19/02
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	carcinogen, initial date 6/11/04
•Toluene	108-88-3	Not Listed
•Xylene	1330-20-7	Not Listed
•Benzene	71-43-2	carcinogen, initial date 2/27/87
•Ethanol	64-17-5	carcinogen, initial date 4/29/11 (in alcoholic beverages)
•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	86290-81-5	Not Listed

U.S. - California - Proposition 65 - Developmental Toxicity

•Naphthalene	91-20-3	Not Listed
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	Not Listed
•Toluene	108-88-3	developmental toxicity, initial date 1/1/91
•Xylene	1330-20-7	Not Listed
•Benzene	71-43-2	developmental toxicity, initial date 12/26/97

Conventional Gasoline with Ethanol

•Ethanol	64-17-5	developmental toxicity, initial date 10/1/87 (in alcoholic beverages)
•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	86290-81-5	Not Listed
U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)		
•Naphthalene	91-20-3	Not Listed
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	Not Listed
•Toluene	108-88-3	7000 µg/day MADL (level represents absorbed dose)
•Xylene	1330-20-7	Not Listed
•Benzene	71-43-2	24 µg/day MADL (oral); 49 µg/day MADL (inhalation)
•Ethanol	64-17-5	Not Listed
•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	86290-81-5	Not Listed
U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)		
•Naphthalene	91-20-3	5.8 µg/day NSRL
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	54 µg/day NSRL (inhalation); 41 µg/day NSRL (oral)
•Toluene	108-88-3	Not Listed
•Xylene	1330-20-7	Not Listed
•Benzene	71-43-2	6.4 µg/day NSRL (oral); 13 µg/day NSRL (inhalation)
•Ethanol	64-17-5	Not Listed
•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	86290-81-5	Not Listed
U.S. - California - Proposition 65 - Reproductive Toxicity - Female		
•Naphthalene	91-20-3	Not Listed
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	Not Listed
•Toluene	108-88-3	female reproductive toxicity, initial date 8/7/09
•Xylene	1330-20-7	Not Listed
•Benzene	71-43-2	Not Listed
•Ethanol	64-17-5	Not Listed
•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	86290-81-5	Not Listed
U.S. - California - Proposition 65 - Reproductive Toxicity - Male		
•Naphthalene	91-20-3	Not Listed
•Cyclohexane	110-82-7	Not Listed
•Ethylbenzene	100-41-4	Not Listed
•Toluene	108-88-3	Not Listed
•Xylene	1330-20-7	Not Listed
•Benzene	71-43-2	male reproductive toxicity, initial date 12/26/97
•Ethanol	64-17-5	Not Listed
•Hexane	110-54-3	Not Listed
•1,2,4-Trimethylbenzene	95-63-6	Not Listed
•Benzine (motor fuel)	86290-81-5	Not Listed

Other Information

- WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Section 16 - Other Information

Revision Date

• 30/November/2015

Preparation Date

• 06/November/2015

Disclaimer/Statement of Liability

• The information herein is given in good faith but no warranty, expressed or implied, is made.

Key to abbreviations

NDA = No Data Available
